

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
28 July 2005 (28.07.2005)

PCT

(10) International Publication Number  
**WO 2005/069020 A1**

(51) International Patent Classification<sup>7</sup>: **G01R 15/16**

Thomas [IE/IE]; Darien, Annacotty, County Limerick (IE).

(21) International Application Number:

PCT/EP2005/000187

(74) Agents: **BROPHY, David et al.**; F.R. Kelly & Co., 27 Clyde Road, Ballsbridge, Dublin 4 (IE).

(22) International Filing Date: 7 January 2005 (07.01.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

S2004/0005

7 January 2004 (07.01.2004) IE

(71) Applicant (for all designated States except US): **SUPARULES LIMITED** [IE/IE]; Lonsdale Road, National Technology Park, Limerick, Co. Limerick (IE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(72) Inventor; and

(75) Inventor/Applicant (for US only): **SORENSEN,**

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: **VOLTAGE MEASURING DEVICE**



(57) Abstract: A device for measuring alternating voltage in a conductor under test (38) comprises a first set of capacitive voltage sensors 32a-f mounted on an electrically insulating support member. The sensors are disposed on the support member at spaced intervals along a first notional circle and are connected in parallel between an inner signal conductor 33 and a zero voltage reference conductor 37. A second set of capacitive voltage sensors 34a-f are mounted on the support member at spaced intervals along a second notional circle and are connected in parallel between an outer signal conductor 35 and the reference conductor 37. The support member is configured to allow a conductor under test 38 to be introduced into the interior of the device so that the sensors surround the axis of the conductor. Each sensor has a signal electrode 48 connected to the signal conductor and a reference electrode 50 connected to the reference conductor and is orientated with the signal electrode facing the conductor under test. The voltage in the conductor

under test is derived as a function of the voltage across the signal conductor and the reference conductor.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations* AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA,

- *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

- *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*